

# MVP SPECIFICATIONS

| <u>Model</u>                            | <u>2 Group</u>     | <u>3 Group</u>     |
|---|--------------------|--------------------|
| <b>Electrical:</b>                      |                    |                    |
| Voltage, Single Phase                   | 220                | 220                |
| Hertz                                   | 50 / 60            | 50 / 60            |
| Amps - max draw                         | 28 amp             | 36 amp             |
| Cord Plug Rating (UL Listed)            | 30 amp             | 50 amp             |
| <b>Brew &amp; Steam Specifications:</b> |                    |                    |
| Watts per Element, Steam Tank           | 2000 x 2           | 2500 x 2           |
| Total Steam Element Wattage             | 4000               | 5000               |
| Steam Tank Capacity (Liters)            | 7.7                | 12.3               |
| Watts per Element, Brew Tank            | 700 x 2            | 700 x 3            |
| Brew Tank Capacities (Liters)           | 1.9 x 2            | 1.9 x 3            |
| <b>Machine Dimensions:</b>              |                    |                    |
|   | <b>Inches / mm</b> | <b>Inches / mm</b> |
| Height                                  | 21" / 534          | 21" / 534          |
| Width                                   | 30" / 762          | 41" / 1042         |
| Depth                                   | 24" / 610          | 24" / 610          |
| <b>Weights &amp; Dimensions:</b>        |                    |                    |
|   | <b>Lbs / Kgs</b>   | <b>Lbs / Kgs</b>   |
| Machine Weight, Empty                   | 154 / 70           | 190 / 86           |
| Shipping Weight (approximate)           | 240 / 109          | 290 / 131          |
| Boxed Dimensions: L" x W" x H"          | 42" x 32" x 31"    | 50" x 32" x 31"    |
| Boxed Dimensions: L x W x H (mm)        | 1042x762x787       | 1245x813x787       |
| <b>Plumbing (Compression):</b>          |                    |                    |
|   | 3/8" OD            | 3/8" OD            |

- Certified by ETL for Sanitation to NSF / ANSI Standard 4
- Certified by ETL for Electrical Safety to ANSI / UL Standard 197
- Certified by ETL for Electrical Safety to CSA Standard C22.2 No. 109
- Certified by KTL for Korean Licensing Standards
- CE Compliant (By request)
- C-Tick Compliant (By request)

